

Safety data sheet

Natural Gas, refrigerated, liquid

Creation date : 09.05.2005
Revision date : 04.11.2011

Version : 1.2

IE / E

SDS No. : 9453
page 1 / 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

Natural Gas, refrigerated, liquid

EC No (from EINECS): 232-343-9

CAS No: 8006-14-2

Index-Nr.

Chemical formula CH₄ (+ Impurities)

REACH Registration number:

Not available.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial and professional. Perform risk assessment prior to use.

Uses advised against

Consumer use.

1.3. Details of the supplier of the safety data sheet

Company identification

BOC, PO Box 1201, Bluebell, Dublin

E-Mail Address ReachSDS@boc.com

1.4. Emergency telephone number

Emergency phone numbers (24h): 1850 333 435

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification acc. to Regulation (EC) No 1272/2008/EC (CLP/GHS)

Press. Gas (Refrigerated liquefied gas) - Contains refrigerated gas; may cause cryogenic burns or injury.

Flam. Gas 1 - Extremely flammable gas.

Classification acc. to Directive 67/548/EEC & 1999/45/EC

F+; R12

Extremely flammable.

Risk advice to man and the environment

Refrigerated liquefied gas. Contact with product may cause cold burns or frostbite.

2.2. Label elements

- Labelling Pictograms



- Signal word

Danger

- Hazard Statements

H281

Contains refrigerated gas; may cause cryogenic burns or injury.

H220

Extremely flammable gas.

- Precautionary Statements

Precautionary Statement Prevention

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P282

Wear cold insulating gloves/face

shield/eye protection.

Precautionary Statement Response

P377

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381

Eliminate all ignition sources if safe to do so.

P336+P315

Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Precautionary Statement Storage

P403

Store in a well-ventilated place.

Precautionary Statement Disposal

None.

2.3. Other hazards

Contact with liquid may cause cold burns/frost bite.

SECTION 3: Composition/information on ingredients

Substance / Mixture: Substance.

3.1. Substances

Natural Gas, refrigerated, liquid

CAS No: 8006-14-2

Index-Nr.:

EC No (from EINECS): 232-343-9

REACH Registration number:

Not available.

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not applicable.

SECTION 4: First aid measures

4.1. Description of first aid measures

First Aid General Information:

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First Aid Inhalation:

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First Aid Skin / Eye:

In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Immediately flush eyes thoroughly with water for at least 15 minutes. Obtain medical assistance.

First Aid Ingestion:

Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of coordination.

4.3. Indication of any immediate medical attention and special treatment needed

None.

Safety data sheet

Natural Gas, refrigerated, liquid

Creation date : 09.05.2005
Revision date : 04.11.2011

Version : 1.2

IE / E

SDS No. : 9453
page 2 / 5

SECTION 5: Fire fighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry powder. Carbon dioxide. Water fog. Use water spray or fog to control fire fumes.

Unsuitable extinguishing media

Do not use a solid water stream.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products

Incomplete combustion may form carbon monoxide.

5.3. Advice for fire-fighters

Specific methods

If possible, stop flow of product. Move container away or cool with water from a protected position. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Prevent water used in emergency cases from entering sewers and drainage systems. If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.

Special protective equipment for fire-fighters

Normal firefighters' equipment consists of an appropriate SCBA (open-circuit positive pressure compressed air type) in combination with fire kit. Equipment and clothing to the following standards will provide a suitable level of protection for firefighters.

Guideline:

EN 469:2005: Protective clothing for firefighters. Performance requirements for protective clothing for firefighting., EN 15090 Footwear for firefighters., EN 137 Respiratory protective devices — Self-contained open-circuit compressed air breathing apparatus with full face mask — Requirements, testing, marking., EN 443 Helmets for fire fighting in buildings and other structures., EN 659 Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Eliminate ignition sources. Use protective clothing. Consider the risk of potentially explosive atmospheres. Evacuate area. Ensure adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. EN 137 Respiratory protective devices — Self-contained open-circuit compressed air breathing apparatus with full face mask — Requirements, testing, marking.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area. Liquid spillages can cause embrittlement of structural materials.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Only experienced and properly instructed persons should handle gases under pressure. The substance must be handled in accordance with good industrial hygiene and safety procedures. Use

only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Take precautionary measures against static discharges. Purge air from system before introducing gas. Keep away from ignition sources (including static discharges). Do not smoke while handling product. Assess the risk of a potentially explosive atmosphere and the need for explosion-proof equipment. Consider the use of only non-sparking tools. Ensure equipment is adequately earthed. Ensure the complete gas system has been (or is regularly) checked for leaks before use. Refer to supplier's handling instructions. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the container contents.

7.2. Conditions for safe storage, including any incompatibilities

Keep container below 50°C in a well ventilated place. Segregate from oxidant gases and other oxidants in store. Observe all regulations and local requirements regarding storage of containers. Cylinders should be stored in the vertical position and properly secured to prevent falling over. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials. All electrical equipment in the storage areas should be compatible with the risk of potentially explosive atmosphere. Containers should not be stored in conditions likely to encourage corrosion.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit value

Value type	value	Note
TLV (ACGIH)	1.000 ppm	2011

8.2. Exposure controls

Appropriate engineering controls

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Product to be handled in a closed system. Gas detectors should be used when quantities of flammable gases/vapours may be released. Keep concentrations well below lower explosion limits. Keep concentrations well below occupational exposure limits. The substance must be handled in accordance with good industrial hygiene and safety procedures. Consider work permit system e.g. for maintenance activities. Systems under pressure should be regularly checked for leakages. Provide adequate general or local ventilation. The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial hygiene and safety procedures.

Personal protective equipment

Safety data sheet

Natural Gas, refrigerated, liquid

Creation date : 09.05.2005
Revision date : 04.11.2011

Version : 1.2

IE / E

SDS No. : 9453
page 3 / 5

Eye and face protection

Protect eyes, face and skin from liquid splashes. Wear a face-shield when transfilling and breaking transfer connections. Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Full-face mask recommended

Guideline:

EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking

Skin protection

Hand protection

Advice: Wear working gloves and safety shoes while handling containers., Wear cold insulating gloves.

Guideline: EN 511 Protective gloves against cold.

Body protection

Protect eyes, face and skin from contact with product.

Other protection

Wear flame resistant/retardant clothing. Take precautionary measures against static discharges. Wear working gloves and safety shoes while handling containers. ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing. EN ISO 20345 Personal protective equipment - Safety footwear.

Respiratory protection

Not required

Thermal hazards

If there is a risk of contact with the liquid, all protective equipment should be suitable for extremely low temperatures.

Environmental Exposure Controls

Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General information

Appearance/Colour: Colourless liquid.

Odour: None.

Melting point: -182 °C

Boiling point: -161 °C

Flash point: Not applicable for gases and gas mixtures.

Evaporation rate:

Not applicable for gases and gas mixtures.

Flammability range: 4,4 %(V) - 17 %(V)

Relative density, gas (Air=1): 0,6

Solubility in water: 26 mg/l

Partition coefficient: n-octanol/water: 1,09 logPow

Autoignition temperature: 595 °C

Explosive properties:

Explosive acc. EU legislation: Not explosive.

Explosive acc. transp. reg.: Not explosive.

Oxidising properties: Not applicable.

Molecular weight: 16 g/mol

Critical temperature: -82 °C

Relative density, liquid (Water=1): 0,42

9.2. Other information

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May react violently with oxidants., Can form potentially explosive atmosphere in air.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Air, Oxidiser. For material compatibility see latest version of ISO-11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General

No known toxicological effects from this product.

SECTION 12: Ecological information

12.1. Toxicity

Can cause frost damage to vegetation.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The substance is a gas, not applicable.

12.5. Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6. Other adverse effects

Global Warming Potential GWP

When discharged in large quantities may contribute to the greenhouse effect.

25

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required. Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods.

Gases in pressure containers (including halons) containing dangerous substances

EWC Nr. 16 05 04*

Safety data sheet

Natural Gas, refrigerated, liquid

Creation date : 09.05.2005
Revision date : 04.11.2011

Version : 1.2

IE / E

SDS No. : 9453
page 4 / 5

SECTION 14: Transport information

ADR/RID

14.1. UN number
1972

14.2. UN proper shipping name
Natural Gas, refrigerated, liquid

14.3. Transport hazard class(es)
Class: 2
Classification Code: 3F
Labels: 2.1
Hazard number: 223
Tunnel restriction code: (B/D)
Emergency Action Code: 2YE

14.4. Packing group (Packing Instruction)
P203

14.5. Environmental hazards
None.

14.6. Special precautions for user
None.

IMDG

14.1. UN number
1972

14.2. UN proper shipping name
Natural Gas, refrigerated, liquid

14.3. Transport hazard class(es)
Class: 2.1
Labels: 2.1
EmS: F-D, S-U

14.4. Packing group (Packing Instruction)
P203

14.5. Environmental hazards
None.

14.6. Special precautions for user
None.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
Not applicable.

IATA

14.5. Environmental hazards
None.

14.6. Special precautions for user
None.

Other transport information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure adequate ventilation. Ensure compliance with applicable regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Seveso Directive 96/82/EC: Listed

Other regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work
Directive 94/9/EC on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX)
Directive 89/686/EEC on personal protective equipment
Council Directive 67/548/EEC on the approximation of laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances
Directive 1999/45/EC concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations
Directive 97/23/EC on the approximation of the laws of the Member States concerning pressure equipment.
This Safety Data Sheet has been produced to comply with Regulation (EU) 453/2010.

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information

Ensure all national/local regulations are observed. Ensure operators understand the flammability hazard. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Advice

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Details given in this document are believed to be correct at the time of going to press.

Further information

Note:

When using this document care should be taken, as the decimal sign and its position complies with rules for the structure and drafting of international standards, and is a comma on the line. As an example 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand and not one (to three decimal places).

References

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:
European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
Matheson Gas Data Book, 7th Edition.
European Industrial Gases Association (EIGA) Doc. 169/11 Classification and Labelling guide.
National Institute for Standards and Technology (NIST) Standard Reference Database Number 69
The European Chemical Industry Council (CEFIC) ERICards.
ISO 10156:2010 Gases and gas mixtures -- Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Safety data sheet Natural Gas, refrigerated, liquid

Creation date : 09.05.2005
Revision date : 04.11.2011

Version : 1.2

IE / E

SDS No. : 9453
page 5 / 5

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
International Programme on Chemical Safety (<http://www.inchem.org/>)
Substance specific information from suppliers.
Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
2010 Code of Practice for the Safety, Health and Welfare at Work (S.I. No. 619 of 2001).

End of document