

CRYOCLEAN[®] snow. SJ-10 CO₂ snow blasting machine.

- Suitable handling thanks to compact design
- Very low consumption
- For difficult-to-access operations
- Small and powerful
- No electric power supply
(powered pneumatically)



Blasting tool: Ergonomic and light weight



Quick connection of pressurised air and CO₂



Clearly laid out operating panel



Easy operation

Technical data

Rack dimensions - L x W x H	400 mm x 300 mm x 300 mm (15.7" x 11.8" x 11.8")
Rack weight	15.0 kg (33.1 lb)
Compressed air consumption	0.3 to 2 m ³ /min (11 to 71 scf/min)
Compressed air operating pressure	5 to 16 bar (72 to 232 psi)
Compressed air connection	Quick coupling
Compressed air quality	Dry; no oil or particles
Liquid CO ₂ consumption	0.1 to 0.3 kg/min (0.2 to 0.7 lb/min)
Liquid CO ₂ operating pressure	20 to 100 bar (290 to 1,450 psi)
Liquid CO ₂ connection	DIN 477 - W 21.8 x 1/14", customer specific
Blasting pressure	2 to 16 bar (29 to 232 psi)
Sound power level	80 to 110 dB(A)

BOC

The Priestley Centre, 10 Priestley Road, The Surrey Research Park, Guildford, Surrey GU2 7XY, United Kingdom
Tel +44 1483 579 857, Fax +44 1483 505 211, www.BOCOnline.co.uk

CRYOCLEAN® snow. SJ-10 auto CO₂ snow blasting machine.



- Automated cleaning of plastic injection moulds, metal and plastic parts
- Maintenance free
- Easy to automate
- Simple control with 24 V DC signal input
- CO₂ control direct on the jetting pistol

Automated cleaning of plastic parts with CRYOCLEAN® snow



Blaster with robot adapter



Quick connection of pressurised air and CO₂



Supply connectors and additional grounding



Direct 24 V control of CO₂ and compressed air

Technical data

Rack dimensions - L x W x H	400 mm x 300 mm x 300 mm (15.7" x 11.8" x 11.8")
Rack weight	15.0 kg (33.1 lb)
Compressed air consumption	0.3 to 2 m ³ /min (11 to 71 scf/min)
Compressed air operating pressure	5 to 16 bar (72 to 232 psi)
Compressed air connection	Customer specific
Compressed air quality	Dry; no oil or particles
Liquid CO ₂ consumption	0.1 to 0.3 kg/min (0.2 to 0.7 lb/min)
Liquid CO ₂ operating pressure	20 to 100 bar (290 to 1,450 psi)
Liquid CO ₂ connection	DIN 477 - W 21.8 x 1/14", customer specific
Blasting pressure	2 to 16 bar (29 to 232 psi)
Sound power level	80 to 110 dB(A)
Input control (separate signal for compressed air and CO ₂)	24 V DC

BOC

The Priestley Centre, 10 Priestley Road, The Surrey Research Park, Guildford, Surrey GU2 7XY, United Kingdom
Tel +44 1483 579 857, Fax +44 1483 505 211, www.BOCOnline.co.uk